

Pro Studio 66



Classical Profel mid-sized shelf/stand monitor with powerful performance. New custom waveguide, perfectly balanced for high impact near-field monitoring and mastering.

Also perfect as main and surround speakers for stereo and multichannel applications, home studios, workstations, auditorium installations, mobile studios and home entertainment installations.

Like all Profel studio series speakers, the PS66 is shielded from radio frequency disturbances. The speaker's electronic components are protected by safety circuits from possible damages caused by signal overload.

An optional floor-stand is also available.

Pro Studio 66

treble	aluminium dome, 25 mm
bass	polypropylene cone, 170 mm
cross over	4500 Hz
sensitivity	0,7V +/-6 dB
maximum acoustic output short term RMS @ 1m	115 dB SPL
maximum acoustic output peak per pair @ 1m	121 dB SPL
frequency response	45-22000 Hz +/- 3 dB
tone adjustment, treble	+2, 0, -2 dB
tone adjustment, bass	+2, 0, -2 dB
bass field adjustment (low bass)	0, -2 dB, -4 dB
amplifier treble	64W
amplifier bass	64W
gain adjustment	+/- 6 dB
magnetic shielding	no
overload protection	yes
radio frequency shielding	yes
auto stand-by	no
stand-by latency	n.a.
signal input	1 XLR balanced
signal output	1 XLR balanced
power inlet	230V AC
power cord	included
weight	7 kg
cabinet	bass-reflex
dimensions (WxHxD)	190x300x225 mm
black	MDF
white	MDF
silver	n.a.
birch	n.a.
cherry	n.a.
custom colors	on request
accessories	
metal grille	n.a.
soft grille	optional
wall mounting	optional
microphone-stand adapter	n.a.
floor stand	optional, matching color
XLR/RCA adapter	not required
radio frequency shielding	optional
warranty	24 months *

* Profel Oy gives 24 months warranty that applies to the speaker elements and the cabinet for material and production defects. In addition, electronic parts in all active speaker models are also protected by a limited lifetime warranty.